
















## CPU Cooler *High performance thermal solutions*






Choosing the wrong CPU cooler for a system can lead to serious overheating, resulting in system shutdowns and potential damage to CPUs. For industrial applications, the following CPU coolers fit the needs of various operating environments, where different levels of cooling are required.

Desktop Core™ CPU Cooler					
					
	LGA1355/1356/2011				LGA1155/LGA1156
Model Name	CF-1356A-RS	CF-1356B-RS	CF-2011A-RS	CF-2011B-RS	CF-1156A-RS-R11
Description	High performance LGA1355/1356/2011 cooler kit				High performance LGA1155/LGA1156 cooler kit, 1U chassis compatible
CPU Solution	Intel® Xeon® E5-2400		Intel® Xeon® processor E5-2600		Intel® Core™ i5/i3
Socket Solution	LGA1355/1356	LGA1355/1356	LGA2011	LGA2011	LGA1155/LGA1156
Dimensions (mm)	89 x 80 x 27	89 x 90 x 24	89 x 88 x 27.2	89 x 88 x 45.1	89 x 92.6 x 27.4
Material	Copper				Cu
Bearing Type	Two-ball	Ball and Sleeve	Two-ball	Ball and Sleeve	Two-ball
Capability (Watt)	60W	95W	130W	130W	73W
Fan Speed (RPM)	4500	5500	5500	4500	5500
Noise Level (dBA)	51	42	55	42	51
Life Expectancy (hrs)	50000	40000	50000	40000	50000
Weight	55g	50g	55g	50g	422g

Desktop Core™ CPU Cooler			Desktop CPU Cooler		
					
	LGA1155/LGA1156			LGA775 Cooler	
Model Name	CF-1156E-R11	CF-1156C-RS	CF-1156D-RS	CF-775A-RS	CF-775B-RS-R11
Description	High performance LGA1155/LGA1156 CPU cooler, RoHS	Low power LGA1155/LGA1156 cooler kit, RoHS		High performance Two copper pipes LGA 775 CPU cooler, RoHS	High performance 1U LGA 775 CPU cooler, w/ 7010 fan, RoHS
CPU Solution	Intel® Xeon®/Core™ i7/i5/i3	Intel® Core™ i5/i3	Intel® Core™ i7/i5/i3	Intel® Core™2 Quad	Intel® Core™2 Duo
Socket Solution	LGA1155/LGA1156	LGA1155/LGA1156	LGA1155/LGA1156	LGA 775	LGA 775
Dimensions (mm)	90 x 90 x 64	90 x 90 x 33	90 x 90 x 33	92 x 92 x 73	80.5 x 81 x 28.2
Material	Al	Al	Cu+Al	Cu-Al	Cu
Bearing Type	Two-ball	Two-ball	Two-ball	Rifle	Two-ball
Capability (Watt)	95W	45W	65W	130W	90W
Fan Speed (RPM)	5500	3000	3000	3600	4250
Noise Level (dBA)	40.5	33.4	33.4	36.6-39.6	40
Life Expectancy (hrs)	50000	50000	50000	40000	50000
Weight	301g	192g	227g	492g	600g

# CPU Cooler *High performance thermal solutions*

Desktop CPU Cooler					
					
	<b>LGA775 Cooler</b>	<b>Pentium® 4 Cooler</b>			<b>Pentium® 3 Cooler</b>
<b>Model Name</b>	<b>CF-520-RS-R11</b>	<b>CF-478A-RS</b>	<b>CF-478B-RS-R11</b>	<b>CF-514-RS</b>	<b>CF-370A-RS</b>
<b>Description</b>	High performance LGA 775 CPU cooler, RoHS	High Performance Copper Socket 478 CPU Cooler, RoHS	High Performance Heat Pipes Socket 478 1U CPU Cooler, RoHS	High Performance Skiving Intel® Pentium® 4 CPU Cooler, RoHS	High Performance Slim Type Socket 370 CPU Cooler, RoHS
<b>CPU Solution</b>	Intel® Core™2 Duo	Intel® Pentium® 4	Intel® Pentium® 4	Intel® Pentium® 4	Intel® Pentium® 3
<b>Socket Solution</b>	LGA 775	Socket 478	Socket 478	Socket 478	Socket 370
<b>Dimensions (mm)</b>	115 x 115 x 67	92 x 92 x 67	89 x 76 x 26	83 x 70 x 55	50 x 52 x 20
<b>Material</b>	Aluminum Alloy	Cu	Cu-Al	Aluminum Alloy	Cu-Al
<b>Bearing Type</b>	Two-ball	Rifle	Two-ball	Two-ball	Two-ball
<b>Capability (Watt)</b>	<b>115W</b>	<b>115W</b>	<b>86W</b>	<b>86W</b>	<b>40W</b>
<b>Fan Speed (RPM)</b>	4500	3600	4800	4800	5500
<b>Noise Level (dBA)</b>	47.5-51.5	39.6	40	42.4	32.1
<b>Life Expectancy (hrs)</b>	70000	40000	50000	50000	40000
<b>Weight</b>	635g	390g	25g	284g	62g

	CPU cooler	Mobile Core™ i7 CPU Cooler		Mobile CPU Cooler	
					
	<b>BLOWER</b>	<b>PGA989</b>		<b>Pentium® M Cooler</b>	
<b>Model Name</b>	<b>BF-02-RS</b>	<b>CF-989A-RS-R12</b>	<b>CF-989B-RS-R11</b>	<b>CF-479B-RS</b>	<b>CF-518-RS</b>
<b>Description</b>	Bracket Cooling Fan, RoHS	High performance Socket-G (PGA989) smart fan CPU cooler, RoHS	High performance Socket-G (PGA989) CPU cooler, Aluminum, RoHS	High Performance Socket 479, M and P Intel® Pentium® M CPU Cooler, RoHS	High Performance Intel® Pentium® M CPU Cooler, RoHS
<b>CPU Solution</b>	Bracket cooling fan	Intel® Core™ i7/i5/i3	Intel® Core™ i7/i5/i3	Intel® Pentium® M, Core™2 Duo (Mobile)	Intel® Pentium® M
<b>Socket solution</b>		PGA989	PGA989	Socket 479	Socket 479
<b>Dimensions (mm)</b>	112 x 90 x 21	60 x 60 x 27.5	60 x 60 x 27.5	50 x 50 x 16	60 x 60 x 26
<b>Material</b>	Plastic	Cu	Al	Al	Aluminum Alloy
<b>Bearing Type</b>	One-ball	Two-ball	Two-ball	Two-ball	Two-ball
<b>Capability (Watt)</b>		<b>55W</b>	<b>50W</b>	<b>50W</b>	<b>20W</b>
<b>Fan Speed (RPM)</b>	2800	4800	4800	5500	5000
<b>Noise Level (dBA)</b>	28	40	40	30.1	36.1
<b>Life Expectancy (hrs)</b>	45000	50000	50000	50000	50000
<b>Weight</b>	107.5g	255g	26g	19g	116g