



## DP-72

### Small Footprint with Oversized Keys

iKey®'s innovative DP-72 mobile keyboard was designed to accommodate rugged applications in manufacturing, material handling and remote data entry. Its unique, oversized keys are color arranged and feature a roomy layout for convenient gloved-hand use. It features a small-footprint design, mounting holes in its case and a large numeric pad. Like other keyboards in the iKey line, the DP-72 is constructed using a robust polycarbonate case and industrial silicone keypad, sealing it from dust, liquids and corrosives.

The DP-72 keyboard is ideal for cold storage/cold temperature use, with oversize keys, and it's glove-hand friendly. DP-72 is ideal for forklift mounting.

Note: This keyboard is available through Zebra's website. The part number for iKey DP-72 when ordering from Zebra is 9010377.

#### Features:

72-Key Functionality

8 Function Keys

Lightweight ABS Polycarbonate Case

Mounting Holes

USB and PS/2 configurations available

## Product Code DP-72

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axis
CABLE	LENGTH: 9 ft coiled (3m) DESIGN: PS/2 or USB Cable
KEY SWITCH	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4 mm) ACTUATION FORCE: 4.74oz +/- .71oz (135g +/- 20g) FEEDBACK: Tactile with mechanical snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	KEYBOARD: 50mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
WEIGHT	2.00 lbs +/- .10 lbs (0.91 kg +/- 0.05 kg)

WARRANTY	1 Year Limited Warranty
HUMIDITY	100% Humidity Resistant
DIMENSIONS	11.40" x 6.30" x 1.86" (w-h-d) 289.56mm x 160.02mm x 47.24mm
MODEL NUMBERS	DP-72-PS2: With PS/2 cable DP-72-USB: With USB cable