



- Note:
1. Material: SECC
 2. Thickness: 0.6mm, 丝印部分详见附图。
 3. Surface treatment: Pantone Black C 组织纹漆(全烤)。
 4. Break all sharp edges & corners free from burrs, finished part must be free of all deburring shavings and particles.
 5. Nut & Standoff must be precisely firmed.
 6. Unspecified radius is R=2mm.
 7. Unspecified internal radius is R=0.5mm.
 8. (A)~(E) are critical dimensions.

此件上所有印刷颜色: Pantone 877c

Note:
The component should be comply with the prohibit of hazardous substances in the HSF Directive.

Hazardous Substances (管制物质)	Threshold (浓度限值)
Cd(镉)	<100ppm
Pb(铅)	<1000ppm
Hg(汞)	<1000ppm
Cr6+ (六价物)	<1000ppm
PBB(多溴联苯)	<1000ppm
PBDE(多溴联苯醚)	<1000ppm
DEHP(邻苯二甲酸二(2-乙基己基)酯)	<1000ppm
BBP(邻苯二甲酸甲苯基丁酯)	<1000ppm
DBP(邻苯二甲酸丁酯)	<1000ppm
DIBP(邻苯二甲酸二异丁酯)	<1000ppm

REV	DESCRIPTION	SIGN	DATE
1			
2			
3			
4			
5			

RANGE (mm)	Common Tolerance	APPROVE	Mark Wang	2022.01.07	TITLE
0~25	±0.10	CHECK	Mark Wang	2022.01.07	Armorlink Electronics Inc.
25~80	±0.15	DESIGN	Jie Yang	2022.01.07	
80~200	±0.20	DRAWN	Jie Yang	2022.01.07	Fan Bracket 0.6*80
200~400	±0.30	UNIT: mm		SCALE: 1:1	MODEL
400~	±0.40	ANGLE		SIZE: A0	DRPC-240-ULT6
		FILE NO:	41019-2312C2-00-HF		PART NO:41019-2312C2-00-HF