

# Power Adaptors

The following power adaptors can be used with these products: NPort® DE-211/311, NPort® 5100/5200/5400/6150/6250/6450, NPort® W2004, NPort® 2150/2250 Plus, UC-7110/7410/7420, VPort 251



	PWR-12150-CN-S1	PWR-12120-USJP-S2	PWR-12200-DT-S1	PWR-12150-EU-S2	PWR-12150-UK-S2
<b>Input Rating</b>					
I/P	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz	100-240 VAC, 50-60 Hz
<b>Input Plug</b>					
Plug Type	CN	US/JP	–	Euro	UK
<b>Output Rating</b>					
O/P	1.5 A @ 12 VDC	1.2 A @ 12 VDC	2 A @ 12 VDC	1.5 A @ 12 VDC	1.5 A @ 12 VDC
<b>Output Plug</b>					
Connector Type	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.5	S-type 5.5/2.1/7.5	L-type 5.5/2.1/9.0	L-type 5.5/2.1/9.0
Outer Diameter	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm	5.5 ± 0.1 mm
Inner Diameter	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm	2.1 ± 0.1 mm
<b>Physical Characteristics</b>					
Dimensions	70 x 45 x 54 mm	75 x 34 x 72 mm	110.8 x 51.8 x 32 mm	70 x 45 x 66.5 mm	70 x 45 x 60 mm
Weight	200 g	130 g	200 g	200 g	200 g
Cord Length	1800 ± 200 mm	1830 to 1950 mm	1800 ± 200 mm	1800 ± 200 mm	1800 ± 200 mm
<b>Environmental Limits</b>					
Operating Temperature	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)	0 to 40°C (32 to 104°F)
<b>Regulatory Approvals</b>					
Safety	UL/PSE	UL/PSE	UL/CE/FCC/GS/CCC	FCC/ELT/PSE/CE	CE/GS/FCC/PSE/ETL

**A**

Accessories > Power Adaptors